Make ideas real



R&S®ZVH CABLE AND ANTENNA ANALYZER

For more efficiency in the field



Equipped with essential functions and features for efficient, fast and reliable field measurements

Depending on options installed, the R&S®ZVH can be a

- ► Cable and antenna analyzer
- ► Two-port vector network analyzer
- ▶ Power meter
- ► Spectrum analyzer

The perfect choice for

Installation and maintenance of RF transmitter system

RF cable measurement


Antenna measurement General purpose spectrum measurement

| Key specifications | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency range | 100 kHz to 3.6/8 GHz |
| Port output power | 0.3 ms/point |
| Data points | 101 to 1201 points |
| DC bias | yes |
| Measurement mode (standard) | DTF, return loss, VSWR, one-port cable loss |
| Measurement mode (optional) | transmission measurement, vector network analysis, vector voltmeter, spectrum analysis, power meter, power measurement with power sensor, pulse measurement |
| Maximum permissible spurious signal | +17 dBm |
| Battery operation (fully charged) | 3 hours (with HA-Z204) 4.5 hours (with HA-Z206) |
| Weight | 3 Kg |

| Your benefit | Features |
|----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Make the right measurement right away | Wizard function, preconfiguration of settings in advance |
| An expandable platform for every RF handheld measurement application | Expanded modes of operation for field strength measurements, power measurements, network analysis, vector voltmeter, pulse measurements |
| Simple wireless remote operation | ► Free downloadable Android/IOS apps R&S®MobileView (third-party wireless router required) |
| Most efficient instrument in the field | ➤ Sunlight readable display ➤ Wizard streamlines test development ➤ Remote control and data export with free R&S®Instrument View software ➤ Fast switching of measurement modes ➤ SD card and USB port for data storage |



Vector network analysis Ref: 1.0 dB • Att: 10 dB Trace: Clear/Write Suppr: Off TG Att: 10 dB -26.39 dB -10.06 dB -4.77 dB -6.02 dB 2.22 GHz 2.22 GHz Jpper Limit: Threshold ower Limit: Threshold Trace 1 -15.0 --21.0 --14 N --44.0 --74.0 -Span: 25 MHz Center: 2.22 GHz Simultaneous display of four S-parameters (S11, S21, S12, S22).



Project manager/expert centrally creates the test sequences Operator uses the wizard to execute the test sequences Operator shows the measurement result to the project manager/expert and documents it





Rohde & Schwarz GmbH & Co. KG | Europe, Africa, Middle East +49 89 4129 12345 | North America 1 888 TEST RSA (1 888 837 87 72)

Latin America +1 410 910 79 88 | Asia Pacific +65 65 13 04 88 | China +86 800 810 82 28 / +86 400 650 58 96

www.rohde-schwarz.com | customersupport@rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG | PD 5215.3733.32 | Version 02.00 | April 2020 (as)

Trade names are trademarks of the owners | R&S®ZVH Cable and Antenna Analyzer | Data without tolerance limits is not binding

Subject to change | © 2020 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany

| Ordering information | |
|----------------------------------------------|----------|
| Base model | |
| Cable & antenna analyzer, 100 kHz to 3.6 GHz | R&S®ZVH4 |
| Cable & antenna analyzer, 100 kHz to 8 GHz | R&S®ZVH8 |

Included: All models include lithium-ion battery pack, LAN and USB cables, AC power supply, CD-ROM with software and documentation, quick start guide and three-year warranty (one year for battery and accessories)

| Popular options | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Remote control via LAN or USB | R&S®ZVH-K40 |
| Transmission measurement | R&S®ZVH-K39 |
| Vector network analysis | R&S®ZVH-K42 |
| Vector voltmeter | R&S®ZVH-K45 |
| Spectrum analysis | R&S®ZVH-K1 |
| Spectrogram measurement application | R&S®ZVH-K14 |
| Power meter | R&S®ZVH-K9 |
| D 1 | |
| Popular accessories | |
| Popular accessories Combined open/short/50Ω load calibration standard, DC to 8 GHz | R&S®FSH-Z28 |
| Combined open/short/50Ω load calibration | R&S®FSH-Z28 R&S®FSH-K29 |
| Combined open/short/50 Ω load calibration standard, DC to 8 GHz Combined open/short/50 Ω load calibration | |
| Combined open/short/50 Ω load calibration standard, DC to 8 GHz Combined open/short/50 Ω load calibration standard, DC to 3.6 GHz | R&S®FSH-K29 |
| Combined open/short/50 Ω load calibration standard, DC to 8 GHz Combined open/short/50 Ω load calibration standard, DC to 3.6 GHz Lithium-ion battery pack, 6.75 Ah | R&S®FSH-K29 R&S®HA-Z206 |