

R&S® SpycerNode 2u12

STORAGE SERVER

Specifications

Description

The R&S® SpycerNode 2u12 is a storage server for media and entertainment applications. With its perfect size as a building block, it is easy to lift, install and deploy. IT managers appreciate features such as two-digit front panel shelf ID, activity and status indicators for all key components, alarms and lockable carriers. With the no single point of failure design, advanced data security and support for dual ported NL-SAS and dual ported SSD drives, the R&S® SpycerNode 2u12 is ready to fulfill a wide range of applications.

Key facts

- Software-defined storage system
- Single namespace
- Scalable data and hardware architecture
- Advanced erasure coding data protection
- Advanced 12 Gbit/s SAS implementation
- 80 PLUS® gold certified power efficiency conversion

Specifications

System configuration		<ul style="list-style-type: none"> • 2 HU rackmount • 12 drives per chassis • dual I/O modules per enclosure (main and JBOD) • Intel Xeon processor • DDR4 DIMM • internal 256 Gbyte M.2 module • mini-SAS HD ports main to JBOB interconnectors • dual ported drive technology
Connectivity per controller		
100 Gigabit Ethernet network	main unit	2 × QSFP data ports
10 Gigabit Ethernet network	main unit	2 × RJ-45 data ports
1 Gigabit Ethernet network	main unit	3 × RJ-45: two data ports, one management port to BMC
USB	main unit	2 × USB 3.0 connectors (rear)
Serial port	main unit	1 × RCA 3.5 mm audio serial port
Video port	main unit	1 × mini HDMI™ port
Expansion	main unit	2 × 12G mini SAS HD

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.



Environmental conditions		
Temperature	operating temperature range	+5 °C to +40 °C (+35 °C above 2000 m)
Relative humidity	operating	20 % to 80 % non-condensing
Altitude	operating	0 m to 3000 m
	nonoperating	-300 m to 12192 m
Vibration	random, operating	0.21 g (RMS)
	random, nonoperating	1.04 g (RMS)
	relocation, swept sine	0.3 g (RMS)
Shock	operating	5 g, 10 ms half sine
	nonoperating	30 g, 10 ms half sine
Acoustics	operating sound power level	≤ 6.5 B LWAd (re 1 pW) at +23 °C ambient
Power rating		
Rated voltage		100 V to 240 V AC
Rated frequency		50/60 Hz
Power consumption	maximum main unit	875 W (100 V to 240 V AC)
	maximum JBOD unit	690 W (100 V to 240 V AC)
	average	
BTU	maximum main unit	2999 BTU/h
	maximum JBOD unit	2355 BTU/h
	average	
Product conformity		
Safety certification	for USA and Canada	in line with UL 60950-1
	for Europe	in line with EN 60950-1
	for CB	in line with IEC 60950-1
Electro Magnetic compatibility (EMC)	North America	CFR 47 part 15, subpart B, class A; CES/NMB-003 class A
	Europe	in line with EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3
Standard marks	North America	FCC, UL, cUL, ICES/NMB-003 class A
	Europe	CE
	China	CCC (PSU only)
	Taiwan	BSMI
	Korea	MSIP (formerly KCC)
	Japan	VCCI
	Australia/New Zealand	RCM (formerly C-tick)
Dimensions and weight		
Dimensions	W × H × D	48.30 cm × 8.89 cm × 63.00 cm (19 in × 3.5 in × 24.8 in)
Weight	including drives	max. 26 kg (57.2 lb)
Rackmounting		
Rails		universal rackmounting kit

Ordering information

Designation	Type	Order No.
R&S®SpycerNode 2u12 storage server, main unit	R&S®SNO2U12	2902.3608.02
R&S®SpycerNode 2u12 storage server, JBOD unit	R&S®SNO2U12JB	2902.3614.02
R&S®SpycerNode 2u12 storage server, HDD bundle 96 Tbyte	R&S®SNO-B100 HDD BUNDLE 96TB (12)	2902.3620.02

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Europe, Africa, Middle East +49 89 4129 12345

customersupport@rohde-schwarz.com

North America 1 888 TEST RSA (1 888 837 87 72)

customer.support@rsa.rohde-schwarz.com

Latin America +1 410 910 79 88 | customersupport.la@rohde-schwarz.com

Asia Pacific +65 65 13 04 88 | customersupport.asia@rohde-schwarz.com

China +86 800 810 82 28 | +86 400 650 58 96

customersupport.china@rohde-schwarz.com



R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG

Trade names are trademarks of the owners

PD 5216.0421.22 | Version 01.00 | November 2019 (ja)

R&S®SpycerNode 2u12 Storage Server

Data without tolerance limits is not binding | Subject to change

© 2019 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany