R&S®UAS Universal Antenna Stand

Versatile antenna stand for different antenna types



Description

The R&S[®]UAS is designed for a diverse range of antennas. It has been customized by our engineers based on customer feedback.

Used primarily in EMC anechoic chambers, a key feature of the R&S®UAS is its functionality as it caters to different types of antennas.

The R&S°UAS comes with an antenna adapter that is compatible with medium-sized Rohde&Schwarz EMC antennas. The R&S°UAS-B01 22 mm diameter tubemount antenna adapter (mounted directly on the standard R&S°UAS antenna adapter) is optionally available for other third-party antennas.

Customizable antenna adapter types are available on request.

The R&S°UAS also comes with the optional R&S°UAS-B02 pneumatic polarization kit, which can be remotely operated by using the R&S°OSP open switch and control platform together with the R&S°OSP-B103 digital I/O module and the R&S°EMC32 EMC measurement software.

Key facts

- I Highly maneuverable with four casters
- Nonreflective attribute with Delrin®
- Movable boom to accommodate longer antennas
- Easy height adjustment
- Manual polarization with quick-lock feature
- Optional R&S®UAS-B02 pneumatic polarization kit
- Supports most Rohde & Schwarz EMC antennas out of the box
- Indoor and outdoor test site compatibility



Product Flyer | Version 02.00

Universal Antenna Stand	R&S®UAS	5611.5012.02
22 mm Diameter Tube- Mount Antenna Adapter	R&S®UAS-B01	5611.5229.02
Pneumatic Polarization Kit	R&S®UAS-B02	5611.5235.02
Third-party antenna adapters		Please contact your local sales office.

Туре

Order No.

Ordering information

Designation

Specifications		
Base unit		
Adjustable boom height	0.25 m to 2.0 m, manual adjustment	
Polarization	0°, 90°, manual, pneumatic (optional)	
Payload	max. 7 kg	
Material	Delrin®, fiberglass	
Casters	yes	
Overall dimensions	720 mm × 1170 mm × 2020 mm (2.36 ft × 3.84 ft × 6.63 ft)	
Antenna stand weight	20 kg (44.09 lb)	
Accessories	includes adapter for medium-sized Rohde&Schwarz EMC antennas	
R&S®UAS-B02 pneumatic p	polarization kit option	
Operating voltage	28 V	
Operating pressure	5 bar to 6 bar (max. 10 bar)	
Control	solenoid valve	
Control cable connector	25-pin, d-sub	
Accessories included	 Plastic tubing, length: 50 m Control cable, length: 10 m Solenoid valve Mounting kit 	



R&S®UAS universal antenna stand with R&S®UAS-B02 pneumatic polarization kit.

Rohde & Schwarz GmbH & Co. KG

Europe, Africa, Middle East | +49 89 4129 12345
customersupport@rohde-schwarz.com
North America | 1 888 TEST RSA (1 888 837 87 72)
customer.support@rsa.rohde-schwarz.com
Latin America | +1 410 910 79 88 | customersupport.la@rohde-schwarz.com
Asia Pacific | +65 65 13 04 88 | customersupport.asia@rohde-schwarz.com
China | +86 800 810 82 28 | +86 400 650 58 96
customersupport.china@rohde-schwarz.com
www.rohde-schwarz.com

R&S® is a registered trademark of Rohde&Schwarz GmbH&Co. KG
Trade names are trademarks of the owners
PD 3607.4829.32 | Version 02.00 | June 2017 (sk)
R&S®UAS Universal Antenna Stand
Data without tolerance limits is not binding | Subject to change
© 2016 - 2017 Rohde&Schwarz GmbH&Co. KG | 81671 Munich, Germany



3607.4829.32 02.00 PDP 1