

R&S®SML

Signal Generator

Specifications

Supplement to data sheet PD 0758.1664.32

For R&S®SML instruments equipped with attenuator 1090.4607.42/43, instead of the value quoted in the data sheet, the following specifications of the R&S®SML apply.

Amplitude modulation

AM distortion ⁸⁾ at AF = 1 kHz

m = 30 % < 1 %

m = 80 % ¹¹⁾ < 2 %

⁸⁾ With option R&S®SML-B3 only for $f > 10$ MHz.

¹¹⁾ With attenuator 1090.4607.42/43 only for $f \geq 500$ kHz.

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Europe, Africa, Middle East +49 89 4129 12345

customersupport@rohde-schwarz.com

North America 1 888 TEST RSA (1 888 837 87 72)

customer.support@rsa.rohde-schwarz.com

Latin America +1 410 910 79 88 | customersupport.la@rohde-schwarz.com

Asia Pacific +65 65 13 04 88 | customersupport.asia@rohde-schwarz.com

China +86 800 810 82 28 | +86 400 650 58 96

customersupport.china@rohde-schwarz.com



R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG
Trade names are trademarks of the owners | Subject to change
PD 5215.2172.22 | Version 01.00 | May 2017 (we)
R&S®SML Signal Generator, Supplement to data sheet
© 2017 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany