



ROHDE & SCHWARZ

Test and Measurement
Division

Release Notes

Noise Test

Application Firmware R&S FS-K30

Release 4.71

with Service Pack 1

for R&S FSP, FSU, FSQ, FSG, FSMR, FSUP
Analyzer Firmware V4.7x

New Features:

- Added file browser to trace export dialog
- Added MMEMory:STORE:TRACE SCPI command

Release Note Revision: 2

Printed in the Federal
Republic of Germany

Contents

History	2
General Topics	3
Compatibility of the R&S FS-K30 Noise Application Firmware with other Firmware Releases	3
Firmware Update of the R&S FS-K30	4
Enabling the Application Firmware via License Key Code Entry	4
New Functions in version 4.71 SP1	5
Improvements	5
Known Issues	5
IEC/IEEE Bus only	5
Modified Functions.....	5
Modifications to the Operating Manual	6
Modified Chapters for manual operation	6
Modified Chapters for remote operation.....	7
Customer Support.....	8
Technical support – where and when you need it	8
Up-to-date information and upgrades	8

History

Date	Rel Note Rev	Changes
11 November 2013	1	First revision for Noise Application Firmware 4.71 SP1
12 January 2016	2	FSQ version V4.75 SP7 added.

General Topics

Compatibility of the R&S FS-K30 Noise Application Firmware with other Firmware Releases

The following table shows the compatible versions of the basic analyzer firmware and the Noise Application Firmware:

Table of compatible versions:

R&S FS-K30 Application Firmware	R&S FSP Basic Firmware	R&S FSU Basic Firmware	R&S FSQ Basic Firmware	R&S FSMR Basic Firmware	R&S FSUP Basic Firmware	R&S FSG Basic Firmware
4.71 SP1	-	4.71 SP5	4.75 SP7 4.75 SP5	-	-	4.79 SP5
4.70 SP1	-	4.71 SP5	4.75 SP5	-	-	4.79 SP5
4.70	-	4.71	4.75	-	-	4.79
4.60 SP2	-	4.61 SP3	4.65 SP3	-	-	4.69 SP3
4.60 SP1	-	4.61 SP2	4.65 SP2	-	-	4.69 SP2
4.60	-	4.61	4.65	-	-	4.69
4.51	4.50 SP1	4.51 SP1	4.55 SP2	-	-	4.59 SP1
4.50	4.50	4.51	4.55	-	-	4.59
4.40	4.40	4.41	4.45	-	4.47	4.49
4.30	4.30	4.31	4.35	4.36 SP3	4.37 SP3	4.39
4.20 SP1	4.20	4.21	4.25	4.26	4.27	4.29
4.20	-	-	-	-	-	4.29
4.10 / 4.10 SP1	4.10	4.11	4.15	4.16 SP1	4.17	-
4.00	4.00	4.01	4.05	4.06	-	-
3.90	3.90	3.91	3.95	3.96	3.99/3.97	-
3.80	3.80	3.81	3.85	3.86	-	-
3.70	3.70	3.71	3.75	-	-	-
3.60	3.60	3.61	3.65	3.66 SP1	-	-
3.50	3.50	3.51	3.55	-	-	-

R&S FS-K30 Application Firmware	R&S FSP Basic Firmware	R&S FSU Basic Firmware	R&S FSQ Basic Firmware	R&S FSMR Basic Firmware	R&S FSUP Basic Firmware	R&S FSG Basic Firmware
3.40	3.40	3.41	3.45	-	-	-
3.30	3.30	3.31	3.35	-	-	-
3.28	3.20	3.21	3.25	-	-	-
-	3.10	3.11	3.15	-	-	-

Note: For **R&S FSMR** a system memory of 512MByte is required.

For instruments, shipped with 256MByte system memory, a memory extension FSQ-B512, order number 1157.1590.02, is available.

The system memory size can be easily checked by pressing SETUP – SYSTEM INFO – STATISTICS, item "Memory size".

Firmware Update of the R&S FS-K30

Since basic firmware version 4.2x a ZIP file with the update sets of the basic system firmware and all available applications is provided. This ZIP file is available in the instruments FIRMWARE section, e.g. R&S FSU of the Service Board on GLORIS.

Please follow the steps described in the instrument's basic firmware release note to perform a complete firmware update.

Enabling the Application Firmware via License Key Code Entry

This section can be skipped if the option key was entered once.

After installing the application firmware package a license key for validation must be entered. The license key is printed either on a label on the rear panel of the instrument or delivered as a part of the R&S FS-K30 Noise application firmware package.

The key sequence for entering the license key is:

SETUP - GENERAL SETUP – OPTIONS - INSTALL OPTION

Use the numeric keypad to input the license key number and press ENTER.

- On a successful validation the message 'option key valid' will appear. The instrument will perform an automatic reboot.
- If the validation failed, the application firmware is not installed.
The most probable reason will be that the instrument is not equipped with the correct basic firmware version. Therefore a messagebox will appear asking for installation of the correct basic firmware version.
If the application firmware package was not installed prior to entering the license key code, a message will appear asking for installation of the application firmware package.

In any case please make sure that the correct basic firmware version and the application firmware package is installed prior to entering the license key code.

New Functions in version 4.71 SP1

- Added file browser to trace export dialog
- Added MMEMory:STORe:TRACE SCPI command

Improvements

The version numbers in brackets indicate the version in which the issue was observed for the first time.

1. [V4.71] **Correction crash occurring after edition of the frequency list.**
2. [V4.60] **Print: use user defined colors for printing.**
3. [V4.60] **Auto Ref Level: increased level headroom to prevent overloading.**

Known Issues

The version numbers in brackets indicate the version in which the issue was observed for the first time.

IEC/IEEE Bus only

1. [V3.90] **[SENSe:]CONFigure:MODE commands**

[SENSe] is not optional for these commands when using the short form: "CONF:MODE" as it conflicts with the "CONFigure" subsystem.

Workaround: Do not omit SENSE for these commands.

Modified Functions

The behaviour of the following functions changed compared to earlier versions [the number in brackets indicates the firmware version that introduced the individual change]:

1. [V3.60] **ASCII Trace export available**
2. [V3.70] **Increased number of digits in table of results**
3. [V3.80] **X-axis scale is configurable between RF and IF frequencies**
4. [V3.80] **Roll key direction is same as the spectrum analyzer**
5. [V4.10] **One marker is supported for noise and gain trace.**
6. [V4.10] **Binary trace data export supported.**
7. [V4.10] **Memory traces supported via SCPI.**
8. [V4.10] **Additional enhancement labels OVLD, EXREF, EXT, SGL and PA.**

9. [V4.10] Optimized print colours.

Print functionality is using the optimized print colours for better view.

10. [V4.10] Trace Export shows all data values in one line

Trace Export function now provides useful array of data. All data values for one frequency point are displayed in the same line.

11. [V4.20] Support for new instrument model R&S FSG.**12. [V4.20 SP1] Added Print Table hardcopy functionality.****13. [V4.30] Added support for the Application recovery feature.****14. [V4.50] Support for option External Mixer B21.****15. [V4.51] Single frequency measurement.****16. [V4.60] Auto Switch Off setting for External Generator Control.****17. [V4.70] Print: use user defined colors for printing.****18. [V4.70] Auto Ref Level: increased level headroom to prevent overloading.****19. [V4.70] Remote command INITiate:CONTinuous supported.****20. [V4.70 SP1] Negative frequency offsets may now be entered for external generator control.****21. [V4.71 SP1] Added file browser to trace export dialog.****22. [V4.71 SP1] Added MMEMoRY:STORe:TRACe SCPI command.**

Modifications to the Operating Manual

The R&S FS-K30 Noise application functions are included in a separate manual set. Please refer to the following order numbers:

- 1157.2316.03 (German and English)

Modified Chapters for manual operation

None

Modified Chapters for remote operation

MMEMory:STORe<1|2>:TRACe 1 to 4,<file_name>

This command stores the selected trace (1 to 4) in a file with ASCII format. The decimal separator (decimal point or comma) for floating-point numerals contained in the file is defined with the command

FORMat:DEXPort:DSEParator.

The file name includes indication of the path and the drive name. Indication of the path complies with DOS conventions.

Example

"MMEM:STOR:TRAC 3,'A:\TEST.DAT'" 'Stores trace 3 in the file 'TEST.DAT' on a disk.

Characteristics

*RST value: -

SCPI: device-specific

Mode: all

This command is an event and therefore has no *RST value and no query

Customer Support

Technical support – where and when you need it

For quick, expert help with any Rohde & Schwarz equipment, contact one of our Customer Support Centers. A team of highly qualified engineers provides telephone support and will work with you to find a solution to your query on any aspect of the operation, programming or applications of Rohde & Schwarz equipment.

Up-to-date information and upgrades

To keep your instrument up-to-date and to be informed about new application notes related to your instrument, please send an e-mail to the Customer Support Center stating your instrument and your wish. We will take care that you will get the right information.

Europe, Africa, Middle East

Phone +49 89 4129 12345
customersupport@rohde-schwarz.com

North America

Phone 1-888-TEST-RSA (1-888-837-8772)
customer.support@rsa.rohde-schwarz.com

Latin America

Phone +1-410-910-7988
customersupport.la@rohde-schwarz.com

Asia/Pacific

Phone +65 65 13 04 88
customersupport.asia@rohde-schwarz.com

China

Phone +86-800-810-8828 / +86-400-650-5896
customersupport.china@rohde-schwarz.com