Make ideas real



R&S®HM7042-5 TRIPLE POWER SUPPLY

Basic power supply at affordable price



The perfect choice for

Education Research & design

Maintenance & Production testing

| Key specifications | |
|-----------------------------|--------------|
| Total power output | 155.5 W |
| Number of outputs | 3 |
| Voltage output CH1, CH3 | 0 V to 32 V |
| Voltage output CH2 | 0 V to 5.5 V |
| Current output CH1, CH3 | 0 A to 2 A |
| Current output CH2 | 0 A to 5 A |
| Display resolution CH1, CH3 | 10 mV/1 mA |
| Display resolution CH2 | 10 mV/10 mA |
| | |

Key features

- ► High-performance, inexpensive laboratory power supply
- ► Floating, overload and short-circuit proof outputs
- ► Separate voltage and current displays for each output
- ▶ Protection of sensitive loads by current limit or electronic fuse
- ► Pushbutton to activate/deactivate all outputs
- ► Low residual ripple, high output power, excellent regulation
- ► Parallel operation for higher current and serial operation for higher voltage
- ► Temperature-controlled fan

| Your benefit | Features |
|--|--|
| Straightforward operation | All functions can be operated from the front panel; separate rotary knobs for each channel to adjust voltage and current |
| The separate output channels can work like individual power supplies | All channels are galvanically separated and can be combined for higher voltage or current |
| Small, compact and quiet | Combination of primary transformer, secondary switching regulator and additional linear control reduces weight and size |

Parallel & serial operating mode

Because all channels are galvanically separated, they can be combined.

- ▶ In the parallel operating mode, channels can be bundled to achieve higher currents
- ▶ In the serial operating mode, channels can be combined for higher output voltages



| Ordering information | |
|-------------------------|--------------|
| Description | Item |
| Triple power supply | R&S®HM7042-5 |
| 19" rackmount kit, 2 HU | R&S®HZ42 |

Included accessories:

The R&S®HM7042-5 includes operating manual, power cable and three-year warranty.

Rohde & Schwarz Representative

Rohde & Schwarz GmbH & Co. KG | Europe, Africa, Middle East +49 89 4129 12345 | North America 1 888 TEST RSA (1 888 837 87 72)

Latin America +1 410 910 79 88 | Asia Pacific +65 65 13 04 88 | China +86 800 810 82 28 / +86 400 650 58 96

www.rohde-schwarz.com | customersupport@rohde-schwarz.com

R&S° is a registered trademark of Rohde & Schwarz GmbH & Co. KG | PD 5215.3540.32 | Version 02.00 | April 2020 (as)
Trade names are trademarks of the owners | R&S°HM7042-5 Triple Power Supply | Data without tolerance limits is not binding
Subject to change | © 2020 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany